


US Power Supply Cord with IEC Connector C17, straight



**Description**

- 1 Function:
- Power Cord, Protection class II
- Pin temperature 60 °C
- custom specific versions on request

**References**

Alternate type: [3-101-170](#)

**Technical Data**

Ratings UL/CSA	10A / 125 VAC; 50/60Hz	appliance inlet/-outlet	C17 acc. to IEC 60320-1
Allowable Operation Temp.	-40°C to 60°C		UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class II
IP-Protection	from front side IP 40 acc. to IEC 60529		
Insulation cover	Suitable for appliances with protection class II acc. to IEC 61140		
Material: Housing	PVC, black		

**All Variants**

Connector		cable				Plug					Order Number
Type	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Type	Country	Standard	Style	Index	
C17		SJT 2x18 AWG	2 x 18 AWG	2.5	black	North America	USA	NEMA 1-15	straight	-	<a href="#">6052.0048</a>

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

**Packaging unit** 50 Pcs

**Mating Inlets/Plugs**

Category / Description

[Appliance Inlet Overview complete](#)



6100-3, Mounting: Screw, Solder terminals or quick connect terminals, Appliance Inlet: IEC C14	<a href="#">6100-3</a>
6100-4, Mounting: Snap-in, Solder terminals or quick connect terminals, Appliance Inlet: IEC C14	<a href="#">6100-4</a>
IEC Appliance Inlet C18, Screw-on Mounting, Front or Rear Side, Solder or Quick-connect Terminal	<a href="#">6102-3</a>
IEC Appliance Inlet C18, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal	<a href="#">6102-5</a>
G-Stecker, Mounting: Appliance Inlet : IEC C14 Without fuse holder	<a href="#">6150</a>
<a href="#">Appliance Inlet further types to 6052.0048</a>	...


[Distribution Unit Overview complete](#)

Distribution Unit for Snap-in Mounting with 1 IEC Appliance Inlet C14 and 1 Appliance Outlet F	0712
Distribution Unit with 1 IEC Appliance Inlet C14 and 2 Appliance Outlets F, Shuttered	4741
Distribution Unit with 1 IEC Appliance Inlet C14 and 4 Appliance Outlets F	4747
Distribution Unit with 1 IEC Appliance Inlet C14 or Power Cord, 5 or 6 IEC Appliance Outlets F and Extra Components	4740

[Distribution Unit further types to 6052.0048](#)
[Power Entry Module Overview complete](#)

DC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 1 or 2 pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, Without fuse holder: Suitable for appliances with protection class I or II	DC11
KEB1, Mounting: Screw, Quick connect terminals 4.8 x 0.8 mm, Without fuse holder: Rocker switch, non-illuminated or illuminated, red, 1-pole, Appliance Inlet: IEC C14, 250 VAC, prewired, Suitable for appliances with protection class I	KEB1
KEB2, Mounting: Screw, Quick connect terminals 4.8 x 0.8 mm, Without fuse holder: Rocker switch, non-illuminated or illuminated, 2-pole, Appliance Inlet: IEC C14, 250 VAC, prewired, Suitable for appliances with protection class I	KEB2
1074, Mounting: Solder terminals or quick connect terminals, Without fuse holder: Rocker switch, non-illuminated, black, 1-pole, Appliance Inlet: IEC C14, 250 VAC, Suitable for appliances with protection class I	1074
DC21, Mounting: Screw Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm Appliance Inlet: IEC C14, Without fuse holder:	DC21

[Power Entry Module further types to 6052.0048](#)
[Power Entry Module with line filter Overview complete](#)

KFB1, Mounting: Screw, Front Side, Filter: Standard Version, Without fuse holder: 10 A, Rocker switch: 1-pole, Appliance Inlet: IEC C14, prewired	KFB1
KFB2, Mounting: Screw, Front Side, Filter: Standard and Medical Version, Without fuse holder: 10 A, Rocker switch: 2-pole, Appliance Inlet: IEC C14, prewired	KFB2
DC12, Mounting: Screw, Front-/Rear-Side, Filter, Standard and Medical Version, Without fuse holder: 10 A, Rocker switch: 1 or 2 pole, non-illuminated or illuminated Appliance Inlet: IEC C14, prewired	DC12
DC22 Mounting: Screw, Rear Side, PCB, 10 A, Filter: Standard and Medical Version, Without fuse holder: Rocker switch: 1 or 2 pole, non-illuminated or illuminated, Appliance Inlet: IEC C14, Suitable for appliances with protection class I	DC22
DD12, Mounting: Screw-on mounting, Front Side, Filter, Standard and Medical Version, Fuse holder: 1 or 2 pole, 10 A, Rocker switch: 2-pole, non-illuminated Appliance Inlet: IEC C14, prewired	DD12

[Power Entry Module with line filter further types to 6052.0048](#)


PHASIS

MISSING PICTURE: \\192.168.100.135\EPIMFS\produktion\export\Datasheets\Datasheet\_GST\_PG07\_2\_Varianten\_Export\TOB-  
LER\6052\_0048\2016\_09\_05\08\_13\_54\_946\_466001\DC0002257-001.jpg

PHASE-OUT

MISSING PICTURE: \\192.168.100.135\EPIMFS\produktion\export\Datasheets\Datashet\_GST\_PG07\_2\_Varianten\_Export\TOB-  
LER\6052\_0048\2016\_09\_05\08\_13\_54\_946\_466001\DC0002257-002.jpg

PHASE-OUT

05.09.2016