PS 1161 Test Probe, Ø 2 mm, 6.3 A



See below:

Approvals and Compliances

Description		References	
- Test Probe - Diameter 2.0 mm		Weblinks pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Accessories, Detailed request for product	
Technical Data			
Diameter	2 mm	Resistance to Soldering Heat	260°C / 5 sec acc. to IEC 60068-2-
Rated current	6.3 A		20, Test Tb, method 1A
Admissible switching power	@ 250 Insertions:	Weight	1.1 g
	220 W / max. 5 A or 75 VDC	Material: Housing	Thermoplastic (PC), UL 94V-2
	440 W / max. 5 A or 50 VAC	Surface of contacts	gold plated , Thickness 2.0 µm
	@ 1000 Insertions:		
	100 W / max. 2 A or 75 VDC		
	150 W / max. 5 A or 50 VAC		
Contact resistance	$< 7\text{m}\Omega$ at 20 mV		
Allowable Operation Temperature	-25°C to 70°C		

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC</u>	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]



Diagrams



All Variants

Product group	Color	Order Number
Test Probe	black	0040.1161
Test Probe	red	0040.1162

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/support-tools/stock-check-distributors

Packaging unit

100 Pcs

Mating Outlets/Connectors

Category / Description



Test Jacks & Probes Overview complete

PB 1151, 6.3 A, Test Jack

PB 1151

The specifications, descriptions and illustrations indicated in this document are based on current

product selected for their own applications.